

CE Classification of Characteristics – Windows



Rational Vinduer A/S
Vardevej 140
7280 Sdr. Felding

Type: AURA windows
For use in dwellings and commercial buildings

	Fixed frame 1230 x 1480	Topguided 1230 x 1480	Sidehung 1230 x 1480	Outward opening Terrace door 1230 x 2180		
Resistance to Wind load	npd	npd	npd	npd		
Water tightness – Non shielded (A)	npd	npd	npd	npd		
Water tightness – shielded (B)	npd	npd	npd	npd		
Load bearing capacity of safety devices	npd	npd	npd	npd		
Acoustic Performance	npd	npd	npd	npd		
Thermal Transmittance	W/m ² K 0,70*	W/m ² K 0,78*	W/m ² K 0,78*	W/m ² K 0,78*		
Radiation properties - Solar factor	0,51*	0,51*	0,51*	0,51*		
Radiation properties - Light transmittance	0,72*	0,72*	0,72*	0,72*		
Notes	*The values are calculated for a single sash window 1230 x 1480 with 4-20-4-20-4 standard argon glazing with TGI spacer. The actual thermal transmission coefficient of the product is provided in quotations and order confirmations in accordance with DS/EN 14351-1 +A1:2010, Table E.2, Note d.					
Air tightness	npd	npd	npd	npd		