

## CE Classification of Characteristics – Windows



Rational Vinduer A/S  
Vardevej 140  
7280 Sdr. Felding

Type: Rational AURA<sub>PLUS</sub> windows  
For use in dwellings and commercial buildings

	Fixed frame 1230 x 1480	Topguided 1230 x 1480	Sidehung 1230 x 1480	Outward opening Terrace door 1230 x 2180		
<b>Resistance to Wind load</b>	npd	npd	npd	npd		
<b>Water tightness – Non shielded (A)</b>	npd	npd	npd	npd		
<b>Water tightness – shielded (B)</b>	npd	npd	npd	npd		
<b>Load bearing capacity of safety devices</b>	npd	npd	npd	npd		
<b>Acoustic Performance</b>	npd	npd	npd	npd		
<b>Thermal Transmittance</b>	W/m <sup>2</sup> K 0,70*	W/m <sup>2</sup> K 0,79*	W/m <sup>2</sup> K 0,79*	W/m <sup>2</sup> K 0,79*		
<b>Radiation properties - Solar factor</b>	0,50*	0,50*	0,50*	0,50*		
<b>Radiation properties - Light transmittance</b>	0,72*	0,72*	0,72*	0,72*		
<b>Notes</b>	*The values are calculated for a single sash window 1230 x 1480 with 4-20-4-20-4 standard argon glazing with TGI spacer. The actual thermal transmission coefficient of the product is provided in quotations and order confirmations in accordance with DS/EN 14351-1 +A1:2010, Table E.2, Note d.					
<b>Air tightness</b>	npd	npd	npd	npd		