



Harmonized Product Standard

**BS EN 14351-1:2006 +A2:2016**

## **Declaration of Performance**

Type of construction product:  
Facade windows and Casement doors

**Rationel FORMA  
triple-glazed**

DOP no.:  
**W-EK-UK-20240901**

The performance of the Facade windows and Casement doors in product line Rationel FORMA; triple-glazed are in conformity with the declared in the following pages.

This Declaration of Performance is issued under the sole responsibility of DOVISTA A/S.  
System of assessment and verification of constancy of performance of the construction product:  
(AVCP) System 3

Intended use:  
For domestic and commercial buildings

Manufacturer:  
**DOVISTA A/S**  
Bygholm Søpark 21D, 8700 Horsens, Denmark

Notified Bodies (Test institute):  
NB 1314, NB 1235

Name of authorized representative: DOVISTA (UK) Ltd., VAT No. GB 493346816, MD Brown, Nicholas Julian  
Address, Authorized representative: Ground Floor, THE FORUM, 9 Lancaster Way, Ermine Business Park,  
Cambridge, PE29 6XU +44 01480 759511

Windows and Doors containing Electrical and Electronic Equipment are in conformity with RoHS (Directive 2011/65/EU of the European Parliament and of the Council of 8 June 2011 on the Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment) as amended by Directive 2015/863/EU.


Date:

27 August 2024

---

Horsens

Signed on behalf of DOVISTA A/S



---

Allan Lindhard Jørgensen  
CEO, DOVISTA A/S

## Declaration of Performance Rational FORMA; triple-glazed

	4.2 Resistance to windload	4.5 Water tightness	4.6 Dangerous substances	4.8 Load bearing capacity of safety devices	4.11 Acoustic performance	4.12 * Thermal transmittance	4.13 * Radiation properties	4.14 Air permeability
<b>Opening function</b>								
<b>CDO</b>	<b>Casement door, 1-leaf</b>							
Declared value	1600PA (C4)	600 PA (9A)	None	(350N/60s), optional	NPD	0,78 (W/m2K)	g 0,53 / LT 0,74	600 PA (4)
Classification standard	EN 12210:2000	EN 12208:2000	-	EN 14609:2004	-	-	-	EN 12207:2000
Test standard	EN 12211:2000	EN 1027:2000	-	EN 14609:2004	-	EN ISO 10077-2: 2003/2012	-	EN 1026:2000
Notified body	NB 1314	NB 1314	-	NB 1314	-	NB 1235	-	NB 1314
Test report	Chilt/P12056/15/A 2013	Chilt/P12056/15/A 2013	-	Chilt/P13059/02, P12056/12 2013	-	0108/688346R, 2016-03-23	0108/688346R, 2016	Chilt/P12056/15/A 2013
Tested size (mm), WxH	1200 x 2400	1200 x 2400	-	-	-	1230 x 1480	-	1200 x 2400
<b>FC</b>								
<b>FC</b>	<b>Fixed casement</b>							
Declared value	NPD	600 PA (9A)	None	N/A	NPD	0,78 (W/m2K)	g 0,53 / LT 0,74	600 PA (4)
Classification standard	EN 12210:2016	EN 12208:2016	-	-	-	-	-	EN 12207:2016
Test standard	EN 12211:2000	EN 1027:2000	-	-	-	EN ISO 10077-2: 2003/2012	-	EN 1026:2000
Notified body	NB 1314	NB 1314	-	-	-	NB 1235	-	NB 1314
Test report	BMT/MTP/F12056/10/Rev1/C 2014	BMT/MTP/F12056/10/Rev1/C 2014	-	-	-	0108/688346R, 2016-03-23	0108/688346R, 2016	BMT/MTP/F12056/10/Rev1/C 2014
Tested size (mm), WxH	935 x 1800	935 x 1800	-	-	-	1230 x 1480	-	935 x 1800
<b>FL</b>								
<b>FL</b>	<b>Fixed light</b>							
Declared value	1600PA (C4)	600 PA (9A)	None	N/A	NPD	0,70 (W/m2K)	g 0,53 / LT 0,74	600 PA (4)
Classification standard	EN 12210:2000	EN 12208:2000	-	-	-	-	-	EN 12207:2000
Test standard	EN 12211:2000	EN 1027:2000	-	-	-	EN ISO 10077-2: 2003/2012	-	EN 1026:2000
Notified body	NB 1314	NB 1314	-	-	-	NB 1235	-	NB 1314
Test report	BMT/MTP/F12056/11/Rev1/C 2014	BMT/MTP/F12056/11/Rev1/C 2014	-	-	-	0108/688346R, 2016-03-23	0108/688346R, 2016	BMT/MTP/F12056/11/Rev1/C 2014
Tested size (mm), WxH	2490 x 2400	2490 x 2400	-	-	-	1230 x 1480	-	2490 x 2400

\*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006 +A1:2010.

\*\* Declared values see sheet "4.11, Acoustic performance"

## Declaration of Performance Rationel FORMA; triple-glazed

	4.2 Resistance to windload	4.5 Water tightness	4.6 Dangerous substances	4.8 Load bearing capacity of safety devices	4.11 Acoustic performance	4.12 * Thermal transmittance	4.13 * Radiation properties	4.14 Air permeability
<b>Opening function</b>								
<b>SGO</b>	<b>Side-guided window</b>							
<b>Declared value</b>	1600PA (C4)	600 PA (9A)	None	(350N/60s), optional	**	0,78 (W/m2K)	g 0,53 / LT 0,74	600 PA (4)
<b>Classification standard</b>	EN 12210:2000	EN 12208:2000	-	EN 14609:2004	-	-	-	EN 12207:2000
<b>Test standard</b>	EN 12211:2000	EN 1027:2000	-	EN 14609:2004	SS-EN ISO 10140-1:2021/2:2021	EN ISO 10077-2: 2003/2012	-	EN 1026:2000
<b>Notified body</b>	NB 1314	NB 1314	-	NB 1314	NB 1314	NB 1235	-	NB 1314
<b>Test report</b>	BMT/MTP/F12056/13/Rev1/C 2014	BMT/MTP/F12056/13/Rev1/C 2014	-	Chilt/P13059, 2013-03-25	Chilt/Z12014/Bc/Ar1	0108/688346R, 2016-03-23	0108/688346R, 2016	BMT/MTP/F12056/13/Rev1/C 2014
<b>Tested size (mm), WxH</b>	1000 x 1600	1000 x 1600	-	-	1230 x 1480	1230 x 1480	-	1000 x 1600
<b>SHO</b>	<b>Sidehung window</b>							
<b>Declared value</b>	1600 PA (B4)	600 PA (9A)	None	(350N/60s), optional	**	0,78 (W/m2K)	g 0,53 / LT 0,74	600 PA (4)
<b>Classification standard</b>	EN 12210:2000	EN 12208:2000	-	EN 14609:2004	-	-	-	EN 12207:2000
<b>Test standard</b>	EN 12211:2000	EN 1027:2000	-	EN 14609:2004	SS-EN ISO 10140-1:2021/2:2021	EN ISO 10077-2: 2003/2012	-	EN 1026:2000
<b>Notified body</b>	NB 1314	NB 1314	-	NB 1314	NB 1314	NB 1235	-	NB 1314
<b>Test report</b>	BMT/MTP/F12056/10/Rev1/C 2014	BMT/MTP/F12056/10/Rev1/C 2014	-	Chilt/P13059, 2013-03-25	Chilt/Z12014/Bc/Ar1	0108/688346R, 2016-03-23	0108/688346R, 2016	BMT/MTP/F12056/10/Rev1/C 2014
<b>Tested size (mm), WxH</b>	935 x 1800	935 x 1800	-	-	1230 x 1480	1230 x 1480	-	935 x 1800
<b>SHRO</b>	<b>Sidehung fully reversible window</b>							
<b>Declared value</b>	1600PA (C4)	600 PA (9A)	None	(350N/60s), optional	**	0,78 (W/m2K)	g 0,53 / LT 0,74	600 PA (4)
<b>Classification standard</b>	EN 12210:2000	EN 12208:2000	-	EN 14609:2004	-	-	-	EN 12207:2000
<b>Test standard</b>	EN 12211:2000	EN 1027:2000	-	EN 14609:2004	SS-EN ISO 10140-1:2021/2:2021	EN ISO 10077-2: 2003/2012	-	EN 1026:2000
<b>Notified body</b>	NB 1314	NB 1314	-	NB 1314	NB 1314	NB 1235	-	NB 1314
<b>Test report</b>	BMT/MTP/F12056/13/Rev1/C 2014	BMT/MTP/F12056/13/Rev1/C 2014	-	Chilt/P13059, 2013-03-25	Chilt/Z12014/Bc/Ar1	0108/688346R, 2016-03-23	0108/688346R, 2016	BMT/MTP/F12056/13/Rev1/C 2014
<b>Tested size (mm), WxH</b>	1000 x 1600	1000 x 1600	-	-	1230 x 1480	1230 x 1480	-	1000 x 1600

\*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006 +A1:2010.

Copyright DOVISTA A/S

\*\* Declared values see sheet "4.11, Acoustic performance"

## Declaration of Performance Rationel FORMA; triple-glazed

	4.2 Resistance to windload	4.5 Water tightness	4.6 Dangerous substances	4.8 Load bearing capacity of safety devices	4.11 Acoustic performance	4.12 * Thermal transmittance	4.13 * Radiation properties	4.14 Air permeability
<b>Opening function</b>								
<b>TGO</b>	<b>Top-guided window</b>							
<b>Declared value</b>	1600PA (B4)	600 PA (9A)	None	(350N/60s), optional	**	0,78 (W/m2K)	g 0,53 / LT 0,74	600 PA (4)
<b>Classification standard</b>	EN 12210:2000	EN 12208:2000	-	EN 14609:2004	-	-	-	EN 12207:2000
<b>Test standard</b>	EN 12211:2000	EN 1027:2000	-	EN 14609:2004	SS-EN ISO 10140-1:2021/2:2021	EN ISO 10077-2: 2003/2012	-	EN 1026:2000
<b>Notified body</b>	NB 1314	NB 1314	-	NB 1314	NB 1314	NB 1235	-	NB 1314
<b>Test report</b>	BMT/MTP/F12056/09/Rev1/C 2014	BMT/MTP/F12056/09/Rev1/C 2014	-	Chilt/P13059, 2013-03-25	Chilt/Z12014/Bc/Ar1	0108/688346R, 2016-03-23	0108/688346R, 2016	BMT/MTP/F12056/09/Rev1/C 2014
<b>Tested size (mm), WxH</b>	1797 x 1568	1797 x 1568	-	-	1230 x 1480	1230 x 1480	-	1797 x 1568
<b>THRO</b>	<b>Tophung reversible window</b>							
<b>Declared value</b>	1600PA (C4)	600 PA (9A)	None	(350N/60s), optional	**	0,78 (W/m2K)	g 0,53 / LT 0,74	600 PA (4)
<b>Classification standard</b>	EN 12210:2000	EN 12208:2000	-	EN 14609:2004	-	-	-	EN 12207:2000
<b>Test standard</b>	EN 12211:2000	EN 1027:2000	-	EN 14609:2004	SS-EN ISO 10140-1:2021/2:2021	EN ISO 10077-2: 2003/2012	-	EN 1026:2000
<b>Notified body</b>	NB 1314	NB 1314	-	NB 1314	NB 1314	NB 1235	-	NB 1314
<b>Test report</b>	BMT/MTP/F12056/22/Rev1/C 2014	BMT/MTP/F12056/22/Rev1/C 2014	-	Chilt/P13059, 2013-03-25	Chilt/Z12014/Bc/Ar1	0108/688346R, 2016-03-23	0108/688346R, 2016	BMT/MTP/F12056/22/Rev1/C 2014
<b>Tested size (mm), WxH</b>	1600 x 1600	1600 x 1600	-	-	1230 x 1480	1230 x 1480	-	1600 x 1600

\*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006 +A1:2010.

\*\* Declared values see sheet "4.11, Acoustic performance"

## Declaration Of Performance Rational FORMA; triple-glazed

## \*\* 4.11 Acoustic performance

Glass	Fixed Light	Opening window	Casement door	Door	Sliding door
4-18-4-16-9,5 Energy/Clear/Laminated Energy WE w. Argon	-	39 (-1;-5)	-	-	-
4-18-4-18-8,8 Energy/Clear/Laminated SOUND Energy WE w. Argon	-	41 (-1;-5)	-	-	-
4-20-4-18-6 Energy/Clear/Energy WE w. Argon	-	38 (-1;-5)	-	-	-
4-20-4-18-6,4 Toughened Energy/Clear/Laminated Energy WE w. Argon	-	39 (-1;-6)	-	-	-
4-20-4-18-6,8 Toughened Energy/Clear/Laminated Energy WE w. Argon	-	39 (-3;-8)	-	-	-
4-20-4-20-4 Energy/Clear/Energy WE w. Argon	-	34 (-1;-5)	-	-	-
6,8-16-4-16-8,8 Laminated Energy/Clear/Laminated Energy WE w. Argon	-	40 (-1;-5)	-	-	-
6-18-4-16-8,8 Toughened Energy/Clear/Laminated SOUND Energy WE w. Argon	-	42 (-1;-5)	-	-	-